



Corrigendum

Corrigendum to “Probabilistic fatigue life prediction
of multidirectional composite laminates”
[Composite Structures 69 (2005) 11–19]

Yongming Liu, Sankaran Mahadevan *

Department of Civil and Environmental Engineering, Vanderbilt University, Box 1831-B, Nashville, TN 37235, USA

The author regrets that in the above article Eqs. (6) and (7) were printed incorrectly. They are now reproduced correctly, below:

$$D_i = \sqrt{\frac{1}{(N_{fi}^1)^2} + \frac{1}{(N_{fi}^2)^2} + \frac{1}{(N_{fi}^6)^2} + \frac{1}{N_{fi}^1 N_{fi}^2}} \quad (6)$$

$$D = \sum_{i=1}^K D_i = \sum_{i=1}^K n_i \sqrt{\frac{1}{(N_{fi}^1)^2} + \frac{1}{(N_{fi}^2)^2} + \frac{1}{(N_{fi}^6)^2} + \frac{1}{N_{fi}^1 N_{fi}^2}} \quad (7)$$

DOI of original article: [10.1016/j.compstruct.2004.04.012](https://doi.org/10.1016/j.compstruct.2004.04.012).

* Corresponding author. Tel.: +1 615 322 3040; fax: +1 615 322 3365.

E-mail address: sankaran.mahadevan@vanderbilt.edu (S. Mahadevan).